

Neutral Cleaner

FILACLEANER



SAFELY CLEANS ALL STONE, TILE, WOOD AND HOUSEHOLD SURFACES



- NON ACIDIC, DOES NOT CONTAIN AMMONIA OR ALCOHOL
- CONCENTRATED FORMULA: MORE THAN 150 APPLICATIONS PER GALLON



Coverage:

(1 GAL - 3.78 L)

Maintenance 1:200 61,115 sq ft (5,678 m²)

Init. Cleaning of Stone 1:30 2,040 sq ft (198 m²)

Coverage rates are indicative and per coat.



Packaging:

1 GAL (3,78 L) 3 plastic bottles per box

1 QT (946 ml) 5 plastic bottles per box

WHAT IT'S FOR

- A gentle cleaner for all wall and floor coverings.
- Safe for pretreated and sensitive surfaces.
- Essential for the post installation cleaning of acid sensitive material such as marble, limestone and travertine.

ADVANTAGES

- Cleans without damaging the surface. When highly diluted (1:200) it leaves no residues and does not require rinsing.
- Highly concentrated: can be diluted according to use.
- Ideal for the maintenance of waxed surfaces.
- When diluted 1:200 can be used in floor cleaning machines.
- Ideal for laminated surfaces.
- Pleasant fragrance.

HOW TO USE IT

FILACLEANER is a pH neutral, concentrated cleaner that can be used on all surfaces, even the most delicate, without fear of damaging them. FILACLEANER is essential for post installation cleaning of acid sensitive materials such as polished natural stone or polished agglomerates. FILACLEANER has various uses according to its dilution and the type of material treated. **As a maintenance cleaner for all types of floors:** dilute 1 capful of FILACLEANER per gallon (1:200) for a no rinse application. For more intense dirt, dilute 1-2 cups per gallon of water (1:30) and rinse. **For the initial washing of stone floors:** FILACLEANER is the ideal product for the first cleaning after installing polished stone (marble, travertine, granite, polished cast stone, etc.). Dilute FILACLEANER 1:30 and apply to the floor with a long handled brush or floor polisher and soft pad. Mop up the residue with cloths or wet vac then rinse thoroughly. For use with floor washing machines: dilute FILACLEANER 1:200 (a cap per gallon). Pour the solution into the tank. CAUTION: Do not use FILACLEANER on carpet or waxed wood floors. Storage temperature: between 41°F and 86 °F (5° C and 30° C). Must be applied to material at temperatures between 41°F and 86 °F (5° C and 30° C).

Fila Chemicals USA, Corp.
Miami, FL 33172
tel +1-305-513-0708
filausa@filasolutions.com

TOLL FREE 1-844-FILA123



Recommended by over

200 INTERNATIONAL TOP BRANDS

manufacturers of materials for floors and wall coverings

filasolutions.com