

# Water Repellent Sealer Water Based

## HYDROREP ECO



### FILA GREEN LINE

**FILA**<sup>®</sup>  
surface care solutions

**TERRACOTTA, QUARRY TILE, EXPOSED BRICK, UNPOLISHED STONE, PLASTER, AND CONCRETE**



**GUARDS AGAINST ALGAE, MOLD AND EFFLORESCENCE.**

**IDEAL FOR EXTERIOR SURFACES.**

### WHAT IT'S FOR

- Creates a water repellent barrier without altering the material's natural finish.
- Guards the surface against algae, mold and efflorescence.
- Prevents wear caused by weather damage.
- Protects while preserving at least 90% surface breathability.

### ADVANTAGES

- Is not affected by residual humidity: can be applied 24-48 hours after initial cleaning, significantly reducing application time.
- Blocks the growth of algae in accordance with UNI EN ISO 846: 1999 standards.
- Does not alter the frost resistance of terracotta.
- Ideal for the protection of exterior surfaces.
- UV resistant.

### HOW TO USE IT

**Ready to use**, no dilution necessary.

**Instructions:** On a clean, dry surface apply an even, generous coat of **HYDROREP ECO** with a brush or airless sprayer. Apply the product until the surface is fully saturated. Before the product dries completely, pat dry with a clean cloth to remove any residue. The surface is dry to the touch after just 4 hours. Should stubborn residue remain, wait for the product to dry and remove using a white pad and **FILAPS87** diluted 1:10.

**Application with airless sprayer:** Do not inhale fumes and use only in well ventilated areas. Refer to the safety information sheet for the necessary personal protective equipment (PPE).

**Caution:** Before application, test **HYDROREP ECO** on a small, inconspicuous area of the surface or loose sample to check for any changes in color. Do not apply the product outdoors if rain is in the forecast. If it starts raining during the application, stop and cover the treatment area immediately. Avoid surface pooling. Do not apply on areas with surface moisture or exposed to direct sunlight. The product is effective after 24 hours and reaches maximum protection 10 days after application.

**Storage temperature:** between 41°F and 86°F (5°C and 30°C). Must be applied at temperatures between 50°F and 86°F (10°C and 30°C).



#### Coverage:

1 Liter (1.06 QT)

**Terracotta, exposed brick, quarry tile, natural**

**stone, plaster** › 107-215 sq.ft. (10-20 m<sup>2</sup>)

**Concrete** › 86-107 sq.ft. (8-10 m<sup>2</sup>)

*Coverage rates are indicative and per coat.*



#### Packaging:

5 Liter (5.28 QT) 4 bottles per box

Fila Chemicals USA, Corp.  
Miami, FL 33172  
tel +1-305-513-0708  
filausa@filasolutions.com

TOLL FREE 1-844-FILA123



Recommended by over

**200 INTERNATIONAL TOP BRANDS**

manufacturers of materials for floors and wall coverings

[usa.filasolutions.com](http://usa.filasolutions.com)