



- TERRACOTTA
- QUARRY TILES
- POLISHED MARBLE AND AGGLOMERATES
- UNPOLISHED MARBLE AND AGGLOMERATES
- CONCRETE



WHAT IT'S FOR

- Removes oily and greasy stains from terracotta, quarry tiles, natural stone, granite, agglomerates, tumbled marble, pebbles, cobblestones, concrete.

ADVANTAGES

- A user friendly spray stain remover.
- Easy to use: just spray and wipe.
- Highly effective on outdoor terracotta either untreated or treated with non filming products.
- Leaves no traces if used on fresh stains.
- Ideal also for quarry tile and natural stone
- Cleans stains stuck into cracks where other stain removers just can't reach.
- Guaranteed performance also on untreated surfaces.

HOW IT'S USED

Do not dilute: ready to use.

Application:

1. Spray at a distance of 6 in (15 cm), keeping the can at an angle of approx. 45°.
2. Leave to dry for a few minutes. It absorbs grease deposits and then dries, leaving a thin layer of white powder on the floor.
3. Remove with a brush.
4. Wipe with a wet cloth.

Repeat application if traces remain.

Caution:

For wax treated floors, remove the wax from the whole tile after removing the stain, then restore the wax coating.

Packaging

8.5 fl oz (250 ml) aerosol cans in box of 12.

PRECAUTIONS

- Keep out of the reach of children.
- Dispose of the container properly after use.
- Extremely flammable.

TEMPERATURE

Storage temperature: between 41° F (5° C) and 77° F (25° C).
Must be applied to material at temperatures between 41° F (5° C) and 77° F (25° C).

LABELLING

IRRITATION

Warning: DANGER!

Hazard statements: Extremely flammable aerosol. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat / sparks / open flames / hot surfaces. No smoking. Wear protective gloves / protective clothing / eye protection / face protection. Call a POISON CENTER or doctor / physician if you feel unwell. Dispose of contents / container in accordance with official regulations.

TECHNICAL INFORMATION

Appearance: pressurized container

Odour: characteristic

Density: 0.68 kg/litre

Propellant flash point: below 32° F

The information above reflects our latest technical know-how and is the outcome of ongoing laboratory research and testing. However, some factors are beyond our control. It is essential to integrate our suggestions with your own on-site preliminary tests and check. Fila accepts no liability for improper use of its products.